



Combi-Line

☆☆☆☆



RECOMMENDED INSURABLE RATING
Up to \$35,000



ECB-S CERTIFIED TO RESISTANCE GRADE S2
Certified protection against burglary



FIRE RESISTANCE GRADE LFS 30
Certified 30 minute protection against fire



CL410



CL420



CL440



CL460



Combi-Line



CL410-CL460 safety cabinets **Combi-Line**

- Tested and certified protection against burglary and fire
- ECB-S certified to Resistance Grade S2
- Security level S2 according to DIN EN 14450
- Fire resistance LFS 30 according to EN 15659 - 30 minutes fire protection for paper
- Fire protective material according to DIN 4102
- Composite insulation in front of the door leaf provides heat protection for the lock and bolts
- Double-walled construction
- Internal hinge
- Lateral locking through 25 mm diameter strong round bolts
- All-over gripping rail on the hinge side
- Prepared for both wall and floor fixing - fixing materials included
- Body and door black
- 1 shelf included as standard
- ECB-S certified safe lock according to EN class A
- Programmable electronic combination lock
- 1 programmable admin code and 1 programmable user code
- 1,000,000 different codes possible
- Keyed Model (K) supplied with 2 x Keys (1 million key differs)

Version - E (Electronic)

Article	Exterior H x W x D	Interior H x W x D	Door H x W	Weight (kg)	Volume (l)
CL 410 E	320 x 435 x 380	205 x 320 x 232	205 x 265	44,0	15,0
CL 420 E	360 x 495 x 445	245 x 380 x 297	245 x 325	55,0	27,0
CL 440 E	560 x 495 x 445	445 x 380 x 297	445 x 325	77,0	50,0
CL 460 E	820 x 495 x 445	694 x 380 x 297	694 x 324	111,0	78,0



E (Electronic) SPECIFICATIONS:

Electronic combination lock SecuTronic, Vds tested, ECB-S certified according to B/EN 1300 class B, 1.000.000 different combinations possible, 4 x batteries supplied (type: LR 06 AA). The locking armature protrudes 13 mm

Version - K (Keyed)

Article	Exterior H x W x D	Interior H x W x D	Door H x W	Weight (kg)	Volume (l)
CL 410 K	320 x 435 x 380	205 x 320 x 232	205 x 265	44,0	15,0
CL 420 K	360 x 495 x 445	245 x 380 x 297	245 x 325	55,0	27,0
CL 440 K	560 x 495 x 445	445 x 380 x 297	445 x 325	77,0	50,0
CL 460 K	820 x 495 x 445	694 x 380 x 297	694 x 324	111,0	78,0



K (Keyed) SPECIFICATIONS:

Security safe lock "SecuSafe", Vds tested, ECB.S certified according to EN 1300 class A, 9 levers, more than 1.000.000 key differs.

Size Options



CL410



CL420



CL440



CL460



Licensed Security
No. 786-555-705

ABATE SAFE CO.

1800 01 91 71 sales@abatesafe.com.au

www.abatesafe.com.au